

30x60
20x60

Ceramic Surface



RAK
CERAMICS

Breviara	06
Chemalite	06
Crema Royale	08
Fume	08
Mont Real	10
New Diano	12
New Onyx	12
Onyx Avion	12
Racha	16
Tuscany	16
Stromboli	18
Ambra	22
Cristal	24
Nuance	24
London	26
Park Wood	28
Tour	28

RAK
CERAMICS



30x60

30x60

Breviara

RED BODY CERAMIC TILES
Glossy • Rectified • Smooth / Light Structure



breviara grey



breviara grey mosaic decor light structure

Chermalite

RED BODY CERAMIC TILES
Glossy • Rectified • Smooth




chermalite white


Name	Code	Size(CM)	Name	Code	Size(CM)
breviara grey	A14RZBRE-GYo.GoR	30x60	chermalite white	A14RZCHM-WHo.GoR	30x60
breviara grey mosaic decor	A14RZBRE-GYo.GRR	30x60			

Sizes (cm)	Thickness (mm)	Pieces X	M² X	Kg X	X Sq. Pallet	M² X Sq. Pallet	kg X Sq. Pallet
30x60	9,50	5	1,62	28,00	60	97,2	1695,00

SIZES



30x60 cm
11.81"x23.62"



30x60 cm
11.81"x23.62"
decor



Wall: Breviara Grey 30x60 cm and Breviara GreyDecor 30x60 cm

30x60

Crema Royale | Fume

Crema Royale

RED BODY CERAMIC TILES
Glossy • Rectified • Smooth / Light Structure



crema royale beige




crema royale beige line decor light structure

Fume

RED BODY CERAMIC TILES
Glossy • Rectified • Smooth / Light Structure




fume white




fume white line decor light structure

SIZES




30x60 cm
11.81"x23.62"



30x60 cm
11.81"x23.62"
decor

Name	Code	Size(CM)	Name	Code	Size(CM)
crema royale beige	A14RZCRL-BEo.GoR	30x60	fume white	A14RZFUM-WHo.HoR	30x60
crema royale beige line decor	A14RZCRL-BEo.GLR	30x60	fume white line decor	A14RZFUM-WHo.HLR	30x60

Sizes (cm)	Thickness (mm)	Pieces X	M² X	Kg X	X Sq. Pallet	M² X Sq. Pallet	kg X Sq. Pallet
30x60	9.50	5	1.62	28.00	60	97.2	1695.00



Wall: Crema Royale Beige 30x60 cm And Crema Royale Beige Line Decor 30x60 cm

Mont Real

RED BODY CERAMIC TILES
Matt • Rectified • Smooth / Heavy Structure




mont real light grey




mont real grey



mont real light beige



mont real light grey wave decor heavy structure



mont real light beige wave decor heavy structure



mont real grey geometric decor heavy structure



mont real beige geometric decor heavy structure


Name	Code	Size(CM)	Name	Code	Size(CM)
mont real light beige	A14RMTRL-LBE.MoXoR	30x60	mont real light beige wave decor	A14RMTRL-LBE.MWXoR	30x60
mont real light grey	A14RMTRL-LIG.MoXoR	30x60	mont real beige wave decor	A14RMTRL-BEE.MGXoR	30x60
mont real grey	A14RMTRL-GRY.MoXoR	30x60	mont real light geometric decor	A14RMTRL-LIG.MWXoR	30x60
			mont real grey geometric decor	A14RMTRL-GRY.MGXoR	30x60

Sizes (cm)	Thickness (mm)	Pieces X	M² X	Kg X	X Sq. Pallet	M² X Sq. Pallet	kg X Sq. Pallet
30x60	9.50	5	1.62	28.00	60	97.2	1695.00

SIZES



30x60 cm
11.81"x23.62"




30x60 cm
11.81"x23.62"
decor



Wall: Mont Real Beige 30x60 cm, Mont Real Beige Geometric Decor 30x60 cm



Wall: New Diano Beige 30x60 cm,
New Diano Beige Line Decor 30x60 cm



Wall: Onyx Avion Ivory 30x60 cm and
Onyx Avion Ivory Line Decor 30x60cm.

30x60

New Diano

RED BODY CERAMIC TILES
Glossy • Rectified • Smooth / Light Structure



new diano beige



new diano beige line decor light structure

New Onyx

RED BODY CERAMIC TILES
Glossy • Rectified • Smooth / Light Structure



New onyx ivory



New onyx ivory line decor light structure

Onyx Avion

RED BODY CERAMIC TILES
Glossy • Rectified • Smooth / Light Structure



onyx avion ivory



onyx avion ivory line decor light structure

SIZES



30x60 cm
11.81"x23.62"



30x60 cm
11.81"x23.62"
decor



Wall: New Onyx Ivory 30x60 cm,
New Onyx Ivory Line Decor 30x60 cm

Name	Code	Size(CM)	Name	Code	Size(CM)
new diano beige	A14RZND-Beo.GoR	30x60	new onyx ivory	A14RZNON-IVo.GoR	30x60
new diano beige line decor	A14RZND-Beo.GLR	30x60	new onyx ivory line decor	A14RZNON-IVo.GLR	30x60
onyx avion ivory	A14RZOAV-IVo.GoR	30x60			
onyx avion ivory line decor	A14RZOAV-IVo.GLR	30x60			

Sizes (cm)	Thickness (mm)	Pieces X	M ² X	Kg X	X Sq. Pallet	M ² X Sq. Pallet	kg X Sq. Pallet
30x60	9.50	5	1.62	28.00	60	97.2	1695.00

Racha

RED BODY CERAMIC TILES
Glossy • Rectified • Smooth / Heavy Structure



racha white



racha white wave decor

heavy structure

Tuscany

RED BODY CERAMIC TILES
Matt • Rectified • Smooth



tuscany beige



tuscany light beige


Name	Code	Size(CM)	Name	Code	Size(CM)
racha white	A14RRACH-WHE.GoXoR	30x60	tuscany beige	A14RZTUS-BEO.GoR	30x60
racha white wave decor	A14RRACH-WHE.GWXoR	30x60	tuscany light beige	A14RZTUS-LBE.GoR	30x60

Sizes (cm)	Thickness (mm)	Pieces X	M² X	Kg X	X Sq. Pallet	M² X Sq. Pallet	kg X Sq. Pallet
30x60	9.50	5	1.62	28.00	60	97.2	1695.00

SIZES



30x60 cm
11.81"x23.62"



30x60 cm
11.81"x23.62"
decor



Wall: Racha White 30x90 cm

Stromboli

RED BODY CERAMIC TILES
 Matt • Rectified • Smooth / Heavy Structure



stromboli light grey



stromboli light beige




stromboli light grey geometric decor heavy structure




stromboli light beige geometric decor heavy structure

SIZES



30x60 cm
11.81"x23.62"



30x60 cm
11.81"x23.62"
decor

Name	Code	Size(CM)	Name	Code	Size(CM)
stromboli light beige	A14RSRL-LBE.MoXoR	30x60	stromboli light beige geometric decor	A14RSRL-LBE.MGXoR	30x60
stromboli light grey	A14RSRL-LIG.MoXoR	30x60	stromboli light grey geometric decor	A14RSRL-LIG.MGXoR	30x60

Sizes (cm)	Thickness (mm)	Pieces X	M² X	Kg X	X Sq. Pallet	M² X Sq. Pallet	kg X Sq. Pallet
30x60	9.50	5	1.62	28.00	60	97.2	1695.00

SIZES



30x60 cm
11.81"x23.62"



30x60 cm
11.81"x23.62"
decor



Wall: Stromboli Light Grey 30x60 cm,
Stromboli Light Grey Geometric Decor 30x60 cm



20x60

Ambra

RED BODY CERAMIC TILES
Matt • Straight • Light Structure



ambra white



ambra grey



ambra white brick decor




ambra grey brick decor




ambra white flower decor

SIZES




20x60 cm
7.87"x23.62"



20x60 cm
7.87"x23.62"
decor

Name	Code	Size(CM)	Name	Code	Size(CM)
ambra grey	A26RZABA-GYo.MPU	20x60	ambra grey brick decor	A26RZABA-GYo.MDU	20x60
ambra white	A26RZABA-WHo.MPU	20x60	ambra white brick decor	A26RZABA-WHo.MDU	20x60
			ambra white flower decor	A26RZABA-WHo.MFU	20x60


Sizes (cm)	Thickness (mm)	Pieces X	M ² X	Kg X	X Sq. Pallet	M ² X Sq. Pallet	kg X Sq. Pallet	X Eu. Pallet	M ² X Eu. Pallet	kg X Eu. Pallet
20x60	9.2	11	1.32	22.00	80	105.6	1760.00	60	79.2	1320.00




Wall: Ambra White Brick Decor 20x60 cm, Ambra White Flower Decor 20x60 cm

Cristal

RED BODY CERAMIC TILES
Matt • Straight • Heavy Structure



cristal white



cristal ivory



cristal white line decor



cristal white bevel decor

Nuance

RED BODY CERAMIC TILES
Matt • Straight • Smooth




nuance grey

Name	Code	Size(CM)	Name	Code	Size(CM)
cristal ivory	A26RZCRI-IVO.GoXoU	20x60	cristal white bevel decor	A26RZCRI-WHO.GBU	20x60
cristal white	A26RZCRI-WHO.GoU	20x60	cristal white line decor	A26RZCRI-WHE.GVXoU	20x60
nuance grey	A26RZNUN-GYo.MoU	20x60			


Sizes (cm)	Thickness (mm)	Pieces X	M ² X	Kg X	X Sq. Pallet	M ² X Sq. Pallet	kg X Sq. Pallet	X Eu. Pallet	M ² X Eu. Pallet	kg X Eu. Pallet
20x60	9.2	11	1.32	22.00	80	105.6	1760.00	60	79.2	1320.00



SIZES



20x60 cm
7.87"x23.62"



20x60 cm
7.87"x23.62"
decor



Floor: Cristal White 20x60 cm And Cristal White Bevel Decor 20x60 cm

London

RED BODY CERAMIC TILES
Matt • Straight • Light Structure



london light grey



london ivory



london grey




london grey decor




Name	Code	Size(CM)
london grey	A26RZLND-GYo.MPU	20x60
london grey decor	A26RZLND-GYo.MDU	20x60
london ivory	A26RZLND-IVo.MPU	20x60
london light grey	A26RZLND-LGY.MPU	20x60

Sizes (cm)	Thickness (mm)	Pieces X	M ² X	Kg X	X Sq. Pallet	M ² X Sq. Pallet	kg X Sq. Pallet	X Eu. Pallet	M ² X Eu. Pallet	kg X Eu. Pallet
20x60	9.2	11	1.32	22.00	80	105.6	1760.00	60	79.2	1320.00

SIZES



20x60 cm
7.87"x23.62"



20x60 cm
7.87"x23.62"
decor



Wall: London Grey 20x60 cm, London Grey Decor 20x60 cm. Floor: Hard Wood Mud 19.5x120 cm.

Park Wood

RED BODY CERAMIC TILES
Matt • Straight • Smooth



park wood grey



park wood mid grey



park wood cinnamon

Tour

RED BODY CERAMIC TILES
Matt • Straight • Smooth



tour light grey



tour grey

Name	Code	Size(CM)
park wood grey	A26RZPKW-GYo.MoU	20x60
park wood mid grey	A26RZPKW-MGY.MoU	20x60
park wood cinnamon	A26RZPKW-CIo.MoU	20x60


Name	Code	Size(CM)
tour light grey	A26RZTOU-LGY.MoU	20x60
tour grey	A26RZTOU-GYo.MoU	20x60

Sizes (cm)	Thickness (mm)	Pieces X	M ² X	Kg X	X Sq. Pallet	M ² X Sq. Pallet	kg X Sq. Pallet	X Eu. Pallet	M ² X Eu. Pallet	kg X Eu. Pallet
20x60	9.2	11	1.32	22.00	80	105.6	1760.00	60	79.2	1320.00

SIZES



20x60 cm
7.87"x23.62"



Wall: Plank Wood Mid Grey 20x60 cm,
Floor: Plank Wood Grey 20x60 cm

TECHNICAL FEATURES

RED BODY AND WHITE BODY CERAMIC TILES (BIII):

Red body and white body Ceramic tiles are made with finest quality clays and with chamotte (a ceramic raw material with high percentage of silica). These raw materials are submitted to dry grinding and suitably mixed and wet and then pressed with hydraulic presses. Quick-cycle support firing is obtained via roller kilns reaching temperatures of approximately 1130 °C. After biscuit glazing, the vitrified product is sintered in a single-layer roller kiln at approximately 1030 °C. The resulting wall tiles have an average bending strength that is higher than 16 N/mm² in accordance with the UNI EN ISO10545-4 standard and a water absorption level that is higher than 10 %; they belong to the BIII (GL) group according to the International Standard ISO 13006 and UNI EN 14411 standard. This class of products shows virtually no shrinkage during firing; therefore such dimensional consistency results in extremely easy laying.

ADVICE ON LAYING

Ceramic Red and White body tiles can be laid using either tile adhesives or cement mortar. Under no circumstances should the tiles be wet before laying when using acrylic or vinyl resin based adhesives or two- component organic solvent based adhesives. When laying large sized tiles it is best to adopt the two layer spreading method and, when the laying surface is very large, to provide for suitable expansion joints which must not be spaced more than 4-5 linear meters apart from one another.

IMPORTANT POINTS TO REMEMBER WHILE LAYING THESE TILES

When laying on wet concrete or plaster, leave to dry for at least one week for each centimetre of thickness.

When laying on brick, never lay on tile adhesive measuring more than 4-5 mm in thickness. For laying on flexible supports (for example plasterboard panels, polymer panels, etc.) which may result in movement of the tiles, we advise laying on tile adhesive measuring no more than 2-3 mm in thickness and to use class C2 or D1 glues. For laying on waterproof brick, which prevents the release of damp, we advise laying on tile adhesive measuring no more than 3 mm in thickness and to use class C2 or D1 glues.

Avoid laying without expansion joints or joints where stress due to expansion is released directly onto the tile.

TECHNICAL CHARACTERISTICS - RED BODY AND WHITE BODY CERAMIC TILES (BIII)

	Test Description	Standard Test Method	International Standard ISO 13006	RAK Ceramics Specifications
	Length & Width	BS EN ISO 10545-2	+/- 0.5%	+/- 0.3%
	Thickness	BS EN ISO 10545-2	+/-10%	+/- 5.0%
	Rectangle Squareness	BS EN ISO 10545-2	+/- 0.5%	+/- 0.4%
	Straightness of sides	BS EN ISO 10545-2	+/- 0.5%	+/- 0.3%
	Surface Flatness	BS EN ISO 10545-2	+/- 0.5%	+/- 0.3%
	Water Absorption	BS EN ISO 10545-3	10% < E <= 20%	10% <E <= 18%
	Modulus of Rupture	BS EN ISO 10545-4		
	Thickness > = 7.5mm		>=12 N/mm ²	>=16 N/mm ²
	Thickness < = 7.5mm		>=15 N/mm ²	>=16 N/mm ²
	Breaking Strength	BS EN ISO 10545-4		
	Thickness > = 7.5mm		>=600N	>=650N
	Thickness < = 7.5mm		>=200N	>=400N
	Resistance to surface abrasion	BS EN ISO 10545-7	Manufacturer to state Abrasion Class	Class 2 - 4
	Resistance to Thermal Shock	BS EN ISO 10545-9	No visible defect	No visible defect
	Crazing Resistance	BS EN ISO 10545-11	No crazing	No crazing
	Resistance to chemicals	BS EN ISO 10545-13	No visible effect	No visible effect
	Resistance to stains	BS EN ISO 10545-14	Manufacturer to state class	Stain removed Min. class 4
	Scratch Hardness : (Moh's)	EN 101	-	4 - 6

Note: Shade variation across the batches is inherent to the manufacturing process and the pre-laying colour comparison is recommended

MAINTENANCE AND CLEANING OF TILES

Maintenance of ceramic and porcelain tiles on dry surfaces is relatively easy. RAK Ceramics tiles are highly scratch and stain resistant.

- By regularly sweeping the floor, you can help avoid scratches that small pebbles or sand can create.
- Make it a habit to always wipe the soles of your shoes on a mat before entering the house. Thoroughly wipe up any spills using plain warm water.
- While they are not likely to stain your ceramic tiles, spills may stain the grout between the tiles and if they are left to sit for too long, may also stain the actual tiles.
- Plain water is the ideal cleaner because it leaves no residue if you dry the surface of the tiles thoroughly after cleaning.
- If tiles are left wet after cleaning, there may be some unsightly mineral residue after the water dries, but this can easily be removed by spot cleaning.
- If stains resist cleaning with water alone, you can use a mild acidic solution, such as white vinegar. Use it highly diluted and rinse with plain water then dry.
- As food stains are acidic in nature, try using a mild alkaline solution.
- Use common detergents sparingly, rinse with plain water and dry thoroughly.

RAK CERAMICS CARE EXCLUSIVE POST INSTALLATION CLEANING SERVICE

We have collaborated with Fila, a leading company in cleaning, protection and maintenance of ceramic surfaces to offer an exclusive cleaning service to address our customers post installation concerns.

Cleaning after laying is of vital importance as a lot of unseen debris and reactive chemicals can affect the visual appearance of the ceramic material. With this new service, our customers can take advantage of Fila's professional on-site consultation. For more info please visit www.rakceramics.com



TILE-LAYING RECOMMENDATIONS

All RAK Ceramics products are subject to size and shade variations. Please check the size, batch number, caliber, tone, choice, color, quality of the pieces before the installation, as no claims will be accepted once the tiles are installed.

Place some tiles on the floor - 2 or 3 sqm - and check the overall technical and aesthetic characteristics with care and check if there is enough product to finish the work.

Manufacturer's responsibility is only limited to replacement of defective material if any, prior to fixing of tiles and we will not entertain claim of any nature after the tiles are installed.

Therefore, if any issue is found on the delivered product, the contractor for installation or the client should not install the tiles. The issue should be communicated to RAK Ceramics for investigation and further action for resolution as required.

The substrate must be a compact cement bed. Levelling system ensures flatness between tiles avoiding movements during the mortar setting. This reduces the time for the ceramic laying obtaining a perfect lippage-free finish. Avoid movements between the tiles due to the mortar setting.

The width of grout joints must be established by the installation supervisor, unless grout widths are regulated by national laying standards. The grout colour should be selected according to the colour of the tile. We recommend to select a matching colour. Before using fine-grain coloured grout on lapped, Glossy or brushed products, always test it. If the pigment is very adhesive, it may be very difficult to remove.

We recommend to lay the tiles by using suitable adhesives for each kind of product and surface. As general rule, tiles must be installed in the same position. The minimum joint is 2 mm for rectified tiles, although we suggest a higher joint for big size products. After grouting, remove any excess product as quickly as possible by repeatedly washing the area with a sponge and water.

Steps to follow 1. First, set the tool to the scale according to the ceramic thickness. 2. Introduce the crossheads and continue laying the adjacent tiles. 3. Put the wedges in the crosshead manually. 4. Tighten the wedges with the pliers to level the pieces. 5. Allow for setting for the time recommended by the manufacturer of the adhesive cement. 6. Remove the crossheads. Hit the crosshead with a rubber mallet or with your foot in the direction of the joint. Do not hit the wedges.


The company will not accept any claim if this is due to the problems caused by not following these suggestions and instructions.



LATICRETE IS A RECOMMENDED PARTNER OF RAK CERAMICS

ICONS

COLOUR VARIATIONS



The least amount of shade variation attainable.

INDICATIONS FOR USE



SUGGESTED APPLICATIONS



Residential areas, hotel rooms, bathrooms

Indoor public areas subject to medium pedestrian traffic such as restaurants, bars, offices, shops, hotel public areas, convention rooms.

In printing, colour of the products may differ slightly from actual, pictures are only for reference.

Contact

RAK CERAMICS
P.O. Box 4714, Ras Al Khaimah,
United Arab Emirates (U.A.E.)
Tel.: +971 7 2467000
Fax: +971 7 2445270
Email : info@rakceramics.com

RAKCERAMICS.COM

RAK

CERAMICS

AVAILABLE IN UAE FLAGSHIP SHOWROOMS:

- ABU DHABI (1):** M39, Mussafah, P.O.Box: 44890, Abu Dhabi.
ABU DHABI (2): Salam Street, Opp. ADCB Head Quarters, P.O.Box: 44890, Abu Dhabi.
ABU DHABI (3): Airport road, Plot No. P5, Sector No. W4, Post Office Tower, P.O.Box: 44890, Abu Dhabi.
AL AIN: Al Sanaiya Road, P.O.Box: 18098, Al Ain.
DUBAI (1): Salahuddin Street, Deira, P.O.Box: 56023, Dubai.
DUBAI (2): Sheikh Zayed Road, Umm Al Sheif, P.O.Box: 56023, Dubai.
SHARJAH: King Faisal Street, Industrial Area 4, P.O.Box: 28427, Sharjah.
AJMAN: Sheikh Khalifa Bin Zayed St, P.O.Box: 15743, Ajman.
RAS AL KHAIMAH: Al Jazeera Al Hamra, P.O.Box: 4714, Ras Al Khaimah.0
FUJAIRAH: Muhammed Bin Matar Street, Opposite Grand Sheikh Zayed Mosque, P.O Box 9058, Fujairah.



80023726427
cs.uae@rakceramics.com